

Murcia + Nagel & Donfar

curing oven

The total oven has 4 modules of 3 meters each. Each module has 2 burners = 8 burners in total, running on propane. Height of conveyor from the floor: 880 mm. Position of the varnished seam: on the upper part of the canbody. CANBODY TRANSPORT: Magnetic conveyor made of 120 mm wide aluminium profile with a length of 3 meters. Connections for internal cooling (cooling optional). Drive by motor variator with electronic speed regulation. Fiberglass conveyor belt with tensioning system. Adjustable side guides for diameters 52–153.7 mm. OVEN STRUCTURE: Brackets for supporting the burners, air ducts, flue gas exhaust duct and gas installation. On the lower part tubular supports are included for mounting the air extractor, air blower and pressurized air fan. Safety protections for burners and moving parts according to CE standards. BURNERS: 2 burners per module, incorporating a gas outlet tube, with hot air outlet grille and manifold, made of refractory stainless steel. Height adjustment of burners: min. $880+52+10 = 942$ mm; max. $880+154+10 = 1,044$ mm. AIR DUCTS: Double air circuit, driven by a fan of 790 m³/h and 2 HP power, and extracted air at 1,800 m³/h. Blower for air mixture of 135 m³/h with pressure of 225 mbar, vacuum 185 mbar. Power 1.1 kW with in-line pressure switch. • 1 pneumatic solenoid valve • 1 pressure gauge • 1 air shut-off valve for flame length regulation GAS DUCTS: Burner supply system with: • Gas inlet pressure regulator and gas filter • 1 pressure gauge at gas inlet and 1 pressure gauge at the outlet of the pressure regulator • 1 air-gas mixture regulator • 2 shut-off solenoid valves and 2 fine adjustment valves, 2 venturis • 2 ignition spark plugs and 2 ionization electrodes ELECTRICAL INSTALLATION: Electrical panel including one ignition transformer per burner, one cycle control module per burner, pressure switches for blowers, shut-off solenoid valves in case of burner stoppage, and safety systems. Indicator of possible faults on synoptic panel.

Technical specifications


CazProductNumber CPN	6623
Name	Murcia + Nagel & Donfar
Tooling	83 & 99 mm
Year of Construction	2000
Can / Ends diameter minimum	52 mm
Can / Ends diameter maximum	154 mm
Can shape	round
Speed (up to)	30-60 meters per minute

Videos

Find the video on our website at the following URL:

<https://www.cazander.com/products/6623-murcia-nagel-donfar-niw2-8000-curing-oven>

Photos



Marca		M+N INGENIERIA, S.L.	
Modelo	M+NIQ 2	Tipo	AEROFLOW
Nº Fab.		Comb.	G.N.
Gasto Horario	Máx.	6,2	m3
	Mín.	1,0	m3
Poten. Nominal	Máx.	61,2	KW
	Mín.	10,2	KW
Presión Alimentación	20-40	COLEGIO TÉCNICO	
Tensión Eléctrica	220	LX 195	
Potencia del Motor			KW
		VISADO	